

Up to 245MPa Ecotop Drill エコトップドリル



ランスを回転させチューブ内の堅い詰まりを除去。ランス長さ・ノズル種類は用途により変更が可能です。
Lance is rotated and remove firm backup. Possible to change lance length and kind of nozzle depend on use purpose.

【仕様】 Specifications

使用圧力 Operating pressure	流量 Flow rate	回転数 Rotation	駆動方式 Driving type	空気供給量 Air pressure	空気消費量 Air consumption	重量 Weight	全長 Length
Max. 245MPa (2500kgf/cm ²)	Max. 40L/min	Max. 300rpm	エアモータ駆動 Airdrive	0.55MPa	16.5L/s	7.5kg	3810mm

Up to 300MPa Turbo Nozzle ターボノズル



超高圧水の噴射反力によりノズルヘッドが自回転する超高圧アタッチメントです。
回転速度は簡単に調整ができ、洗浄対象物に応じて変更が可能です。様々なガンの先端に装着し使用します。
The turbo nozzle is a ultra high pressure attachment that nozzle head rotate automatically by injection reaction of ultra high pressure water. It is easy to adjust rotation speed, and possible to change rotation speed depends on a washing object. It install at the tip of various gun and use.

【仕様】 Specifications

使用圧力 Operating pressure	流量 Flow rate	回転数 Rotation	回転方向 Rotation Direction	温度 Temperature	重量 Weight
Max. 300MPa (3000kgf/cm ²)	Max. 46L/min	Max. 4000rpm	右 Right	Max. 95°C	100mm